

Tube Caps & Plugs

These rugged black polyethylene round, square and rectangular tube caps (plug type) are designed to fit inside tubing for both feet and cap applications. The ribbed fins provide a positive fit inside the tube so that they don't fall out. The textured top resists scratches and scarring.



Measure the outside dimension of the tube to order from our spec sheet. Measuring the inside dimension can also help us to recommend the right plug for your application, especially if you have thick wall tubing or pipe. ABS available upon special request on some sizes. For solid legs, use the OD caps shown on page 2. For angled leg applications, we recommend the domed caps (see page 2) or swivel glides (see page 3). White (-WH) available on 1-1/2" size and smaller. Tubing gauge refers to the wall thickness. 18 GA is thin wall (.05") and 5 GA is thick (.21") 10 GA is .134" and 14 GA is .083". Wall thickness is equal to the OD of the tube, minus the ID then divide by 2. (or measure directly using calipers)

Tube Caps, Steel

These nickel plated metal spring caps are available in round and square sizes. The caps have a bright shiny finish. The round caps have a slightly domed top.



P/N (square)	P/N (round)	TUBING O.D.	TUBING GAUGE
IL24D-CAP-SQ	IL24D-CAP-RD	3/8	16-20 GA
IL24C-CAP-SQ	IL24C-CAP-RD	1/2	16-20 GA
IL24B-CAP-SQ	IL24B-CAP-RD	5/8	16-20 GA
IL24A-CAP-SQ	IL24A-CAP-RD	3/4	14-20 GA
IL24-CAP-SQ	IL24-CAP-RD	7/8	14-20 GA
IL25-CAP-SQ	IL25-CAP-RD	1	12-20 GA
IL25A-CAP-SQ	IL25A-CAP-RD	1-1/8	14-20 GA
IL26-CAP-SQ	IL26-CAP-RD	1-1/4	14-20 GA
IL26A-CAP-SQ	IL26A-CAP-RD	1-3/8	14-18 GA
IL27-CAP-SQ	IL27-CAP-RD	1-1/2	14-18 GA
IL27-CAP-SQ-10	IL27-CAP-RD-10	1-1/2	10-14 GA
IL27B2-CAP-SQ	IL27B2-CAP-RD	1-5/8	16-18 GA
IL27B-CAP-SQ	IL27B-CAP-RD	1-3/4	14-18 GA
IL27B-CAP-SQ-10	IL27B-CAP-RD-10	1-3/4	10-12 GA
	IL27B3-CAP-RD	1-7/8	16-18 GA
IL27A-CAP-SQ	IL27A-CAP-RD	2	12-18 GA
IL27A-CAP-SQ-5		2	5-8 GA
IL27A2-CAP-SQ	IL27A2-CAP-RD	2-1/4	10-14 GA
IL27A3-CAP-SQ	IL27A3-CAP-RD	2-3/8	10-14 GA
IL27C-CAP-SQ	IL27C-CAP-RD	2-1/2	12-18 GA
IL27E-CAP-SQ	IL27E-CAP-RD	2-3/4	14-18 GA
IL27E-CAP-SQ-10	IL27E-CAP-RD-10	2-3/4	8-12 GA
	IL27E2-CAP-RD	2-7/8	4-7 GA
IL27F-CAP-SQ	IL27F-CAP-RD	3	12-18 GA
IL27F-CAP-SQ-8	IL27F-CAP-RD-8	3 (5-8 GA SQ)	(8-12 GA RD)
IL27G-CAP-SQ	IL27G-CAP-RD	3-1/8	10-14 GA
IL27H-CAP-SQ	IL27H-CAP-RD	3-1/2	6-12 GA
IL27J-CAP-SQ	IL27J-CAP-RD	3-7/8	4-8 GA
IL27K-CAP-SQ	IL27K-CAP-RD	4	6-11 GA
	IL27K-CAP-RD-18	4	16-20 GA
IL27L-CAP-SQ	IL27L-CAP-RD	4-1/8	7-12 GA
IL27K2-CAP-SQ	IL27K2-CAP-RD	4-1/2	7-11 GA
IL27M-CAP-SQ	IL27M-CAP-RD	4-3/4	6-11 GA
IL27N-CAP-SQ		5	7-11 GA
IL27P-CAP-SQ		6	5-8 GA

P/N (rectangular)	TUBING O.D.	TUBING GAUGE
IL24C-RE-CAP	1/2X1	12-18 GA
IL24C2-RE-CAP	1/2X1-1/2	12-18 GA
IL24B-RE-CAP	5/8X1-3/8	12-18 GA
IL24A-RE-CAP	3/4-1-1/2	12-18 GA
IL24-RE-CAP	1X1-1/2	12-18 GA
IL25-RE-CAP	1x2	14-18 GA
IL25-RE-CAP-10	1x2	10-14 GA
IL25B-RE-CAP	1x2-1/2	12-18 GA
IL25A-RE-CAP	1x3	12-18 GA
IL26-RE-CAP	1-1/4x2	14-20 GA
IL27A2-RE-CAP	1-1/2X2-1/2	12-16 GA
IL27-RE-CAP	1-1/2x3	12-18 GA
IL27A-RE-CAP	2x3	14-20 GA
IL27A-RE-CAP-10	2x3	10-14 GA
IL27C-RE-CAP	2x4	14-20 GA
IL27C-RE-CAP-10	2x4	10-14 GA
IL27D-RE-CAP	2x5	8 GA
IL27D-RE-CAP-10	2x5	10 GA

P/N (square)	P/N (round)	TUBING O.D.	TUBING GAUGE
	IL24C-R-CAP-NKL	1/2	16-18 GA
	IL24B-R-CAP-NKL	5/8	16-18 GA
IL24A-CAP-NKL	IL24A-R-CAP-NKL	3/4	16-18 GA
IL24-CAP-NKL	IL24-R-CAP-NKL	7/8	16-18 GA
IL25-CAP-NKL	IL25-R-CAP-NKL	1	16-18 GA
	IL25A-R-CAP-NKL	1-1/8	16-18 GA
	IL26-R-CAP-NKL	1-1/4	16-18 GA
	IL27-R-CAP-NKL	1-1/2	16-18 GA
	IL27A-R-CAP-NKL	2	16-18 GA



INTERNATIONAL EQUIPMENT COMPONENTS, INC.
 2201 E. Willow St. #D-104, Signal Hill, CA 90755
 562-597-4533, Fax 562-498-2275, www.levelingmounts.com, glides@verizon.net

Tube Caps (OD Type)

These black polyethylene tube caps are designed to fit over the outside diameter (OD). They can be used as caps or feet. The height of the flange is 5/8"



P/N (square)	P/N (round)	TUBING O.D.
	IL24D-RD-CAP-OD	3/8
IL24C-SQ-CAP-OD	IL24C-RD-CAP-OD	1/2
IL24B-SQ-CAP-OD	IL24B-RD-CAP-OD	5/8
IL24A-SQ-CAP-OD	IL24A-RD-CAP-OD	3/4
	IL24-RD-CAP-OD	7/8
IL25-SQ-CAP-OD	IL25-RD-CAP-OD	1
	IL25A-RD-CAP-OD	1-1/8
IL26-SQ-CAP-OD	IL26-RD-CAP-OD	1-1/4
	IL27-RD-CAP-OD	1-1/2
	IL27B2-RD-CAP-OD	1-5/8
	IL27B-RD-CAP-OD	1-3/4
	IL27A-RD-CAP-OD	2
	IL27C-RD-CAP-OD	2-1/2
IL27F-SQ-CAP-OD	IL27F-RD-CAP-OD	3

Domed Tube Caps (Plug Type)

These black polyethylene tube caps have a domed surface which can accommodate any leg angle.

The ribbed fins are flexible allowing these inserts to fit varying wall thicknesses (16-20 gauge).

P/N (square)	P/N (round)	TUBING O.D.
	IL24B-RD-CAP-DOME	5/8
IL24A-SQ-CAP-DOME	IL24A-RD-CAP-DOME	3/4
IL24-SQ-CAP-DOME	IL24-RD-CAP-DOME	7/8
IL25-SQ-CAP-DOME	IL25-RD-CAP-DOME	1
	IL26-RD-CAP-DOME	1-1/4
	IL27-RD-CAP-DOME	1-1/2
	IL27B-RD-CAP-DOME	1-3/4

Octagon Leveler and Tube Insert Sets

These black nylon tube inserts and threaded octagon leveler combinations are designed to fit hollow tubing. They support 200 lb load and adjust 1" height. Also available in steel.



P/N (square)	P/N (round)	TUBING O.D.
IL24A-SQ-OCT		3/4
IL24-SQ-OCT		7/8
IL25-SQ-OCT		1
IL25A-SQ-OCT		1-1/8
	IL26-RD-OCT	1-1/4
IL26A-SQ-OCT	IL26A-RD-OCT	1-3/8
IL27-SQ-OCT	IL27-RD-OCT	1-1/2
IL27B-SQ-OCT	IL27B-RD-OCT	1-3/4
IL27A-SQ-OCT	IL27A-RD-OCT	2
	IL27A2-RD-OCT	2-1/4

Angle Iron Caps

These black polyethylene caps fit standard angle iron (.125" thick steel). They are used as floor protectors and caps to cover sharp edges.



P/N	LEG LENGTH
IL25-CAP-ANGLE	1
IL26-CAP-ANGLE	1-1/4
IL27-CAP-ANGLE	1-1/2

Ball Glides

These black polyethylene ball glides can accommodate any leg angle. They fit over round rod or tubing.




P/N	LEG DIA.	BALL DIA.
IL24E-CAP-BALL	5/16	5/8
IL24C-CAP-BALL	1/2	7/8
IL24B-CAP-BALL	5/8	1



Weld Cup Caps

These white polyethylene caps/feet fit inside standard weld cups for patio chairs. 1/2" tall. The O.D. of the cap should match the I.D. of your feet.

P/N	CAP O.D.
IL26-R-CAP-WELD	1.25
IL27-R-CAP-WELD	1.50



Vinyl Tube Caps

These black vinyl caps are resistant to tearing or splitting. The flexible design allows for stretching onto slightly larger dimensions for a snug fit. Commonly used to cover tube ends and protect threads from moisture and impact damage. They also serve as a reusable mask for painting, plating or powder-coating process. The high gloss material is well suited for decorative applications.



HOLE COVER CAPS

These black plastic (ABS) caps with removable slot covers are used on office furniture and computer desks. Rectangular sizes and Solid hole plugs also available.



P/N (square)	P/N (round)	TUBING O.D.	FLANGE HEIGHT
IL24E-CAP-VNL-SQ	IL24F-CAP-VNL-RD	1/8	1/2
	IL24E-CAP-VNL-RD	1/4	1/2
	IL24D-CAP-VNL-RD	3/8	1/2
IL24C-CAP-VNL-SQ	IL24C-CAP-VNL-RD	1/2	1/2
	IL24B-CAP-VNL-SQ	5/8	1/2
IL24A-CAP-VNL-SQ	IL24A-CAP-VNL-RD	3/4	1/2
	IL24-CAP-VNL-RD	7/8	1/2
IL25-CAP-VNL-SQ	IL25-CAP-VNL-RD	1	1
	IL25A-CAP-VNL-RD	1-1/8	1
IL26-CAP-VNL-SQ	IL26-CAP-VNL-RD	1-1/4	1
	IL26A-CAP-VNL-RD	1-3/8	1
IL27-CAP-VNL-SQ	IL27-CAP-VNL-RD	1-1/2	1
	IL26B-CAP-VNL-RD	1-5/8	1
IL27B-CAP-VNL-SQ	IL27B-CAP-VNL-RD	1-3/4	1
	IL26C-CAP-VNL-SQ	1-7/8	1
IL27A-CAP-VNL-SQ	IL27A-CAP-VNL-RD	2	1
	IL26E-CAP-VNL-RD	2-1/4	1
IL27H-CAP-VNL-SQ	IL27C-CAP-VNL-RD	2-1/2	1
	IL27E-CAP-VNL-RD	2-3/4	1
IL27K-CAP-VNL-SQ	IL27F-CAP-VNL-RD	3	1
	IL27G-CAP-VNL-RD	3-1/4	1
IL27H-CAP-VNL-SQ	IL27H-CAP-VNL-RD	3-1/2	1
	IL27J-CAP-VNL-RD	3-5/8	1
IL27K-CAP-VNL-SQ	IL27K-CAP-VNL-RD	4	1
	IL27L-CAP-VNL-RD	4-1/4	1
IL27K-CAP-VNL-SQ	IL27N-CAP-VNL-RD	4-3/8	1
	IL27P-CAP-VNL-RD	4-7/16	1
IL27K-CAP-VNL-SQ	IL27M-CAP-VNL-RD	4-3/4	1
	IL27T-CAP-VNL-RD	5-1/2	1

P/N (round)	COVER O.D.	HOLE SIZE	FLANGE HEIGHT
IL27-CAP-CMP-SLT	1-1/2	1-1/4	1/2
IL27A-CAP-CMP-SLT	2	1-7/8	1
IL27A2-CAP-CMP-SLT	2-1/4	2	1
IL27F-CAP-CMP-SLT	3	2-1/2	1/2
IL27F2-CAP-CMP-SLT	3	2-3/4	1
IL27H-CAP-CMP-SLT	3-9/16	3-1/4	1

SWIVEL TUBE GLIDES

These black plastic tube glides swivel approx. 30 degrees. Available with solid nylon base or felt base (add - FELT). Also available with non-swivel felt base (replace -SVL with -FELT). (see bottom photo).



P/N (round)	TUBE O.D.	GAUGE	FIN HEIGHT
IL24A-PLUG-SVL	3/4	16-18	1
IL24-PLUG-SVL	7/8	16-18	1
IL25-PLUG-SVL	1	16-18	1
IL25A-PLUP-SVL	1-1/8	16-18	1

ANGLED TUBE GLIDES

These black plastic tube glides have a 5, 15 or 25 degree angle.

P/N (square)	TUBE O.D.	GAUGE	ANGLE
IL24A-PLUG-ANGLE-5	3/4	16-18	5
IL24A-PLUG-ANGLE-25	3/4	16-18	25
IL24-PLUG-ANGLE-5	7/8	16-18	5
IL24-PLUG-ANGLE-25	7/8	16-18	25
IL25-PLUG-ANGLE-15	1	16-18	15

