



**SLANT BASE STUD LEVELERS**


The IEC Slant Base Stud Leveler is ideal for heavy-duty loads. Integrated ball and swivel socket provide a low-friction support interface. Ideal for cabinets, instruments, machinery and equipment.

**Features**

- Solid steel/stainless steel
- Integrated ball and socket
- Adjustable height
- Base adjusts 15° off centerline
- Standard gold iridite zinc finish
- Black oxide or clear chromate options
- Elastomer or non-marring delrin base

**Applications**

- Equipment benches
- Machinery
- Instruments
- Enclosures



**STEEL & STAINLESS STEEL**

Dimensions stated in inches.

Steel	SS	Load	A	B	C	D	E	F
IL2-4G	IL6-4	1400	1/4-20	1/2	45/64	1	5/32	2
IL2-6G	IL6-6	3000	3/8-16	5/8	7/8	1-1/4	3/16	2
IL2-7G	IL6-7	5000	1/2-13	3/4	1-1/8	1-7/8	1/4	2
IL2-8G	IL6-8	6000	5/8-11	7/8	1-1/4	2-1/2	5/16	2
IL2-9G	IL6-9	8000	3/4-10	1-1/16	1-1/2	3	1/2	2
IL2-10G	IL6-10	20000	1-8	1-1/2	1-7/8	4	13/32	4-1/4

**ELASTOMER STEEL & STAINLESS STEEL**

Steel	SS	Load	A	B	C	D	E	F
IL2-4G-P	IL6-4-P	1050	1/4-20	1/2	37/64	1	5/32	2
IL2-6G-P	IL6-6-P	2250	3/8-16	5/8	6/8	1-1/4	3/16	2
IL2-7G-P	IL6-7-P	3750	1/2-13	3/4	1	1-7/8	1/4	2
IL2-8G-P	IL6-8-P	4500	5/8-11	7/8	1-1/8	2-1/2	5/16	2
IL2-9G-P	IL6-9-P	6000	3/4-10	1-1/16	1-3/8	3	1/2	2
IL2-10G-P	IL6-10-P	15000	1-8	1-1/2	1-6/8	4	13/32	4-1/4

**DELTRIN BASE STEEL & STAINLESS STEEL**

Steel	SS	Load	A	B	C	D	E	F
IL4-4W	IL4-4S	200	1/4-20	1/2	45/64	1	5/32	2
IL4-6W	IL4-6S	300	3/8-16	5/8	7/8	1-1/4	3/16	2
IL4-7W	IL4-7S	700	1/2-13	3/4	1-1/8	1-7/8	1/4	2
IL4-8W	IL4-8S	1200	5/8-11	7/8	1-1/4	2-1/2	5/16	2
IL4-9W	IL4-9S	1800	3/4-10	1-1/16	1-1/2	3	1/2	2
IL4-10W	IL4-10S	2400	1-8	1-1/2	1-7/8	4	13/32	4-1/4