



INTERNATIONAL EQUIPMENT COMPONENTS, INC.  
 2201 E. Willow St. #D-104, Signal Hill, CA 90755  
 562-597-4533, Fax 562-498-2275, www.levelingmounts.com, glides@verizon.net

Vibration Control,  
 Bumpers and Anti-  
 skid Feet

P/N (female)	P/N (male)	THREAD	DIA.	HEIGHT	STUD LENGTH (male)
IL300F-1	IL300 M-1X25	6-32	7/16	7/16	1/4
IL301F-1	IL301 M-1X38	6-32	1/2	1/2	3/8
IL302 F-2	IL302 M-2X25	8-32	7/16	7/16	1/4
IL303 F-2	IL303 M-2X3/8	8-32	1/2	1/2	3/8
IL304 F-3	IL304 M-3X3/8	10-32	9/16	1	N/A
IL305 F-3		10-32	3/4	5/8	3/8
IL307F-4	IL306 M-4X1	1/4-20	1	3/8	1
	IL307 M-4X50	1/4-20	1	3/4	1/2
	IL308 M-4X50	1/4-20	1-1/4	3/4	1/2
IL309F-4		1/4-20	1-3/8	3/4	N/A
IL310F-5	IL310 M-5X125	5/16-18	1	3/8	1-1/4
IL312F-5	IL311 M-5X62	5/16-18	1	5/8	5/8
	IL312 M-5X62	5/16-18	1	1	5/8
	IL313 M-5X62	5/16-18	1-1/4	5/8	5/8
	IL314 M-5X62	5/16-18	1-1/2	1	5/8
IL315F-5	IL315 M-6X62	3/8-16	1-1/2	1	5/8
	IL316 M-6X75	3/8-16	2-1/4	1	3/4



These cylindrical vibration and noise dampening rubber feet/bumpers are offered in both male and female thread types. Zinc plated steel stud or socket. The socket depth is 3/8". Most items available in varying durometers from 30 to 70. (standard durometer is 45 +/- 5)

These conical stud type vibration and noise dampening rubber feet/bumpers are offered with a zinc plated steel stud.

P/N	THREAD	MAJOR DIA.	MINOR DIA.	HEIGHT	STUD LENGTH
IL320 -3X50	10-32	1-1/8	5/8	1	1/2
IL321 -4X50	1/4-20	1-1/2	1	1-1/4	1/2
IL322 -5X75	5/16-18	1-1/2	1	1-1/4	3/4
IL323 -5X125	5/16-18	1-1/2	1	1-1/4	1-1/4
IL324 -5FX75	5/16-24	1-1/2	1	1-1/4	3/4
IL325 -5FX175	5/16-24	1-1/2	1	1-1/4	1-3/4
IL326 -6X62	3/8-16	1-1/2	1	1-1/4	5/8
IL327-7X2	1/2-13	2	1-5/8	1-1/4	2



These cylindrical double stud shock, vibration and noise dampening flexible connectors are offered with a zinc plated steel stud. They are designed for compression and shear applications.

P/N	THREAD	DIA.	HEIGHT	DUAL STUD LENGTH
IL330 -0X19	4-40	1/4	9/32	3/16
IL331 -1X25	6-32	7/16	7/16	1/4
IL332 -2X25	8-32	7/16	1/2	1/4
IL332 -2X38	8-32	9/16	1/2	3/8
IL333 -3AX50	10-24	1	1/2	1/2
IL334 -3X38	10-32	3/4	5/8	3/8
IL340 -4X38	1/4-20	3/4	3/8	3/8
IL341 -4X50	1/4-20	1	1/4	1/2
IL342 -4X50	1/4-20	1	1/2	1/2
IL343 -4X50	1/4-20	1	3/4	1/2
IL344 -4X75	1/4-20	1	1	3/4
IL347 -4AX38	1/4-28	3/4	1/2	3/8
IL348 -4AX38	1/4-28	1	3/8	3/8
IL349 -4AX50	1/4-28	1	3/4	1/2
IL350 -5X50	5/16-18	1	3/8	1/2
IL352 -5X50	5/16-18	1	3/4	1/2
IL354 -5X62	5/16-18	1	1	5/8
IL355 -5X50	5/16-18	1	1-1/2	3/4
IL356 -5X75	5/16-18	1	2	1/2



(continued on next page with male/female, dual female and nail-on types)

**For adjustable leveling feet, furniture glides, caps, plugs, felt pads, bumpers, sliders, legs, knobs, vibration and noise control, visit our website at [www.levelingmounts.com](http://www.levelingmounts.com) or call us at 562-597-4533**



INTERNATIONAL EQUIPMENT COMPONENTS, INC.  
 2201 E. Willow St. #D-104, Signal Hill, CA 90755  
 562-597-4533, Fax 562-498-2275, www.levelingmounts.com, glides@verizon.net

**Vibration & Noise Control**

These cylindrical double stud shock, vibration and noise dampening flexible connectors are designed for compression and shear applications. Zinc plated steel stud.

P/N	THREAD	DIA.	HEIGHT	DUAL STUD LENGTH
IL357 -5X50	5/16-18	1-3/8	5/8	1/2
IL358 -5X50	5/16-18	1-3/8	1	1/2
IL359 -5X75	5/16-18	1-3/8	1	3/4
IL360 -5X50	5/16-18	1-3/8	1-1/4	1/2
IL362 -5X1	5/16-18	1-3/8	1	1
IL363 -5X1	5/16-18	1-1/2	1	1
IL370 -6X75	3/8-16	1-3/8	1	3/4
IL371 -6X75	3/8-16	1-3/8	1-1/2	3/4
IL372 -6X62	3/8-16	1-1/2	1	5/8
IL373 -6X62	3/8-16	2	1-5/8	5/8



These cylindrical male stud / female socket shock, vibration and noise dampening flexible connectors are designed for compression and shear applications. Zinc plated steel stud and socket.

P/N	THREAD	DIA.	HEIGHT	MALE STUD LENGTH
IL375 -1X25	6-32	7/16	7/16	1/4
IL376 -2X25	8-32	7/16	7/16	1/4
IL377 -2X38	8-32	9/16	1/2	3/8
IL378 -3X38	10-32	9/16	1/2	3/8
IL379 -3X38	10-32	3/4	5/8	3/8
IL380 -4X50	1/4-20	1	3/4	1/2
IL381 -4X50	1/4-20	1	1	1/2
IL382 -5X50	5/16-18	1	3/4	1/2
IL383 -5X50	5/16-18	1	1	1/2
IL384 -5X62	5/16-18	1-1/4	1	5/8
IL385 -5X62	5/16-18	1-1/2	1	5/8
IL386 -6X62	3/8-16	1-1/2	1-3/8	5/8



These cylindrical dual female socket shock, vibration and noise dampening flexible connectors are designed for compression and shear applications. Zinc plated steel sockets.

P/N	THREAD	DIA.	HEIGHT	SOCKET DEPTH
IL388 -1	6-32	7/16	7/16	1/4
IL389 -2	8-32	9/16	1/2	1/4
IL390 -3	10-32	3/4	5/8	3/8
IL391 -4	1/4-20	1	3/4	3/8
IL391 -4	1/4-20	1	1	3/8
IL392 -5	5/16-18	1	1	3/8
IL393 -6	3/8-16	1-1/2	1	3/8
IL394 -6	3/8-16	1-1/2	1-3/8	3/8



These half spherical vibration and noise dampening nail-on bumpers/feet are available in black or dark brown.

P/N	COLOR	DIA.	HEIGHT	NAIL LENGTH
IL397 -B	BLACK	3/8	7/32	3/8
IL397 -BR	BROWN	3/8	7/32	3/8
IL398 -B	BLACK	1/2	5/16	3/8

**For adjustable leveling feet, furniture glides, caps, plugs, felt pads, bumpers, sliders, legs, knobs, vibration and noise control, visit our website at [www.levelingmounts.com](http://www.levelingmounts.com) or call us at 562-597-4533**